

5000E & SM-10FE

- Created for the specific challenges, such as water flow limitations and protection needs, of wildland firefighting, dust abatement, de-icing, etc.
- Used in conjunction with smaller monitors such as the Sidewinder®
- Constant flow — straight stream, narrow fog (30°), or wide fog (90°) — with spinning teeth
- Either automatic or fixed flow nozzle type available
- Motor (12V or 24V DC available) totally enclosed and sealed
- Manual override standard
- Lightweight Elk-O-Lite® construction with hard anodized finish
- AFFF compatible

Base Size	AVAILABLE STANDARD FLOW RATES (Fixed) GPM (LPM)													STANDARD FLOW RANGE (Automatic) GPM (LPM)	TEETH		Effective Reach at Highest Flow (Ft.)	Weight (Lbs.)	MODEL	
	15 (57)	30 (114)	45 (170)	60 (227)	75 (284)	95 (360)	125 (473)	150 (568)	175 (662)	200 (757)	250 (946)	350 (1325)	400 (1514)	475 (1798)	20 - 120 (76 - 454)	Spinning				None
	PSI (BAR) 100 (6.89)																			
1.5"	•	•	•													•		85	3.1	5000-04E
				•	•	•	•	•								•		124	3.1	5000-14E
									•	•	•	•	•	•		•		150	3.1	5000-24E
															•		•	115	4.9	SM-10FE*

* Suitable for de-icing / anti-icing use

BASE SIZE	FLOW RATES GPM (LPM)	PRESSURE PSI (BAR)	Effective Reach (Feet) @ Highest Flow	Weight (Lbs.)	MODEL
1.5"	15/30/45/60/95/125/150/200/FLUSH (60/120/170/250/360/500/550/750/FLUSH)	100 (6.89)	124	4.7	6000-200E