

XD Handline Nozzle Specifications

CHIEF™ XD HANDLINE NOZZLE TIPS

Nozzle shall be constructed of durable, hard anodized black, lightweight Elk-O-Lite®; shall be single gallonage and constant flow; shall have infinite pattern selection from straight stream to full fog; shall be capable of flushing without shutting down; shall have stainless steel teeth or molded rubber teeth (specify); shall have highly visible, protective urethane bumper; shall have laser etched markings and serial number; shall flow _____ gpm at _____ psi and have rated flow stamped on stem head; shall comply with NFPA 1964.

CHIEF™ XD HANDLINE NOZZLES

Nozzle shall be constructed of durable, hard anodized black, lightweight Elk-O-Lite®; shall be single gallonage and constant flow; shall have infinite pattern selection from straight stream to full fog; shall be capable of flushing without shutting down; shall have stainless steel teeth or molded rubber teeth (specify); shall have highly visible, protective urethane bumper; shall have laser etched markings and serial number; shall have full round aluminum shutoff ball with self-adjusting UHMWPE seats; shall have rugged, forged aluminum bale handle with double stops and color-coded insert; shall have Elk-O-Lite® pistol grip mounted to bottom of shutoff body with color-coded insert (*optional*); shall flow _____ gpm at _____ psi and have rated flow stamped on stem head; shall comply with NFPA 1964.

1.5" XD SHUTOFF

1.5" double drive ball shutoff with 1.375" waterway; shall be constructed of durable, hard anodized black, lightweight, Elk-O-Lite®; shall have full round aluminum shutoff ball with self-adjusting UHMWPE seats; shall have rugged, forged aluminum bale handle with double stops and color-coded insert; shall have Elk-O-Lite® pistol grip mounted to bottom of shutoff body with color-coded insert (*optional*); shall have laser etched markings and serial number; shall have a 1.5" NHT female swivel base with a 1.5" NHT male outlet.

1.5" XD SHUTOFF WITH INTEGRATED SMOOTH BORE

1.5" double drive ball shutoff with 1.375" waterway; shall be constructed of durable, hard anodized black, lightweight, Elk-O-Lite®; shall have full round aluminum ball with self-adjusting UHMWPE seats; the shutoff shall have a _____ size integral smooth bore tip machined into the outlet of the body; shall have rugged, forged aluminum bale handle with double stops and color-coded insert; shall have Elk-O-Lite® pistol grip mounted to bottom of shutoff body with color-coded insert (*optional*); shall have laser etched markings and serial number; shall have a 1.5" NHT female swivel base with a 1.5" NHT male outlet.

2.5" XD SHUTOFF

2.5" double drive ball shutoff with 1.375" waterway; shall be constructed of durable, hard anodized black, lightweight, Elk-O-Lite®; shall have full round aluminum shutoff ball with self-adjusting UHMWPE seats; shall have rugged, forged aluminum bale handle with double stops and color-coded insert; shall have Elk-O-Lite® pistol grip mounted to bottom of shutoff body with color-coded insert (*optional*); shall have laser etched markings and serial number; shall have a 2.5" NHT female swivel base with a 1.5" NHT male outlet.

2.5" XD SHUTOFF WITH INTEGRATED SMOOTH BORE

2.5" double drive ball shutoff with 1.375" waterway; shall be constructed of durable, hard anodized black, lightweight, Elk-O-Lite®; shall have full round aluminum ball with self-adjusting UHMWPE seats; the shutoff shall have a ____ size integral smooth bore tip machined into the outlet of the body; shall have rugged, forged aluminum bale handle with double stops and color-coded insert; shall have Elk-O-Lite® pistol grip mounted to bottom of shutoff body with color-coded insert (*optional*); shall have laser etched markings and serial number; shall have a 2.5" NHT female swivel base with a 1.5" NHT male outlet.

2.5" XD PLAYPIPE

2.5" double drive ball shutoff with 1.375" waterway; shall be constructed of durable, hard anodized black, lightweight, Elk-O-Lite®; shall have full round aluminum shutoff ball with self-adjusting UHMWPE seats; shall have rugged, forged aluminum bale handle with double stops and color-coded insert; shall have two large "U" shaped handles; shall have Elk-O-Lite® ladder hook mounted underneath shutoff (*optional*); shall have laser etched markings and serial number; shall have a 2.5" NHT female swivel base with a 1.5" NHT male outlet.

SHORT BARREL XD SMOOTH BORE

Smooth bore tip shall be constructed of durable, hard anodized black, lightweight Elk-O-Lite®; shall have 1.5" NHT inlet and gradual taper to an outlet size of ____ with an overall tip length of 4.5"; tip shall be protected with a robust EPDM rubber bumper; shall have the rated discharge flow at 50 psi laser etched onto tip barrel; tip barrel shall have knurling for ease of grip and handling.

LONG BARREL XD SMOOTH BORE

Smooth bore tip shall be constructed of durable, hard anodized black, lightweight Elk-O-Lite®; shall have 1.5" NHT inlet and gradual taper to an outlet size of ____ with an overall tip length of 7"; tip shall be protected with a robust EPDM rubber bumper; shall have the rated discharge flow at 50 psi laser etched onto tip barrel; tip barrel shall have knurling for ease of grip and handling.