



NOTE
DIMENSIONS SHOWN ARE APPROXIMATE AND ARE SUBJECT TO MINOR DEVIATIONS AS MAY OCCUR OR BE NECESSARY IN CONSTRUCTION. MINOR DETAILS NOT SHOWN.

- NOTES:**
1. ONAN 25kW SINGLE PHASE PTO DRIVEN GENERATOR LOCATED BETWEEN THE FRAME RAILS
 2. POLISHED S/S SCUFFPLATES ON CAB AND CREW CAB DOOR JAMBS
 3. FLOOR IN CAB AND CREW CAB TO BE PADDED RUBBER
 4. DAVID CLARK 4-POSITION INTERCOM SYSTEM
 5. PIERCE LED LIGHTS IN ALL BODY AND HATCH COMPARTMENTS
 6. TURTLE TILE ON COMPARTMENT AND HATCH COMPARTMENT FLOORS AND SHELVES AND TRAYS

CLEAR DOOR WIDTH KEY

AM/DOR ROLL UP DOORS	-2.14"
GORTITE ROLL UP DOORS	-2.12"
PIERCE DOUBLE LIP DOORS	-4.14"
PIERCE LIFT UP LIP DOORS	-1.12"

(EX: 60" F - 2.14" = 57 3/4" CLEAR)
(F-F) = FRAME TO FRAME

CUSTOMER APPROVAL

APPROVED BY: _____
DATE: _____

REV	DATE	BY	CH

Pierce MANUFACTURING INC.

TITLE: HEAVY DUTY RESCUE NON-WALKIN
FOR: CENTEREACH FIRE DEPARTMENT CENTEREACH, NEW YORK
DWG NO.: **Rev 4**

JOB NO.	-
SCALE	1:24
DATE	12NOV2021
DRAWN BY	MZI
CHECKED BY	-
SHEET SIZE	D
SHEET NO.	1 of 1