



NOTE:
LAP DOORS HAVE BEEN SHOWN IN
HIDDEN LINES TO CLEARLY IDENTIFY THE
EQUIPMENT IN EACH COMPARTMENT. DASHED
LINES ON SIDES ARE DOORS IN OPEN POSITION

NOTE
DIMENSIONS SHOWN ARE APPROXIMATE
AND ARE SUBJECT TO MINOR DEVIATIONS
AS MAY OCCUR OR BE NECESSARY IN
CONSTRUCTION.
MINOR DETAILS NOT SHOWN.

NOTES:
1. ONAN 40kW SINGLE PHASE PTO DRIVEN GENERATOR WITH SPLASH GUARD LOCATED BETWEEN THE FRAME RAILS.

(SIDE ROLL & FRONTAL IMPACT PROTECTION)
MAXIMUM O.A.H.: 11' - 00"

CLEAR DOOR WIDTH KEY	
AMOR ROLL UP DOORS:	-2 1/4"
CORTITE ROLL UP DOORS:	-2 1/2"
PIERCE DOUBLE LAP DOORS:	-4 1/4"
PIERCE LIFT-UP LAP DOORS:	-1 1/2"
(EX: 60" F-F - 2 1/4" = 57 3/4" CLEAR)	
(F-F) = FRAME TO FRAME	

REV	DATE	BY	CH
-	-	-	-

		JOB NO.	PRELIM
		SCALE	DATE
TITLE	HEAVY DUTY RESCUE WALKIN	DRAWN BY	SHD
FOR	ROTTERDAM FIRE DISTRICT #2	CHECKED BY	-
	BID #882	DWG NO.	70277-SH1
		SHEET NO.	1 OF 2